

## ADVERTISEMENT BOOKING & MATERIAL DEADLINES

Issue	Booking Deadline	Material Deadline
Jan/Feb 2021	09 Nov 2020	18 Nov 2020
Mar 2021	08 Jan 2021	19 Jan 2021
Apr 2021	05 Feb 2021	17 Feb 2021
May 2021	10 Mar 2021	19 Mar 2021
Jun 2021	09 Apr 2021	20 Apr 2021
July 2021	06 May 2021	18 May 2021
Aug 2021	09 Jun 2021	18 Jun 2021
Sep 2021	07 Jul 2021	16 Jul 2021
Oct 2021	12 Aug 2021	23 Aug 2021
Nov 2021	09 Sep 2021	20 Sep 2021
Dec 2021	08 Oct 2021	19 Oct 2021

## MECHANICAL SPECIFICATIONS

Size	Trimmed	Type Area	Bleed
Full Page	275 x 205 mm	255 x 185 mm	281 x 211 mm
Double-Page Spread*	275 x 410 mm	255 x 390 mm	281 x 416 mm
Two-third (Vertical)	275 x 130 mm	255 x 120 mm	281 x 136 mm
Half-page (Vertical)	275 x 100 mm	255 x 90 mm	281 x 106 mm
Half-page (Horizontal)	135 x 205 mm	125 x 185 mm	141 x 211 mm
One-third (Vertical)	275 x 68 mm	255 x 58 mm	281 x 74 mm

\* For DPS ad, a gutter allowance of 5 mm per page is recommended (not applicable for front cover reverse gatefold position)

## Technical Specifications on Material Submission

The Advertiser shall submit to SPH Magazines (hereafter referred to as "SPHMAG") a PDF/X-1A compliant file before the material deadline. The following list details the main criteria for ad material, but is not intended to be exhaustive.

For further assistance, please contact: Alice Chee, DID: 6319 6399, email: [siewyuan@sph.com.sg](mailto:siewyuan@sph.com.sg)

### 1. Format & Compatibility

- 1) A PDF file shall be compliant with the **ISO PDF/X-1a:2001** standard as defined by **ISO 15930-1**, colour value as derived from **Fogra 39L** dataset.
- 2) A PDF file must be embedded with output intent profile, i.e. Art paper – Fogra 39L, Woodfree paper – Fogra 29L
- 3) TAC (Total Area Coverage) for any Rich Blacks and/or graphics must not exceed 330% for art paper or 300% for woodfree paper
- 4) Crop marks must appear on PDF, located at least 3mm away from the trim area.
- 5) The size of a PDF file must comply with the specifications of the respective publication. SPHMAG will not be held responsible if any file type or artwork exceeds the type area specified and is trimmed away.
- 6) For Double-page Spread, the type or product shots should be away from gutter area and not split. Any critical cross over should be double imaged across the gutter with an **allowance of 5mm** from each side of the centre. The spread should carry a minimum 10mm common image through the centre of the spread.
- 7) A PDF file must not contain annotations that are set to print.
- 8) A PDF file must not use layers.
- 9) No object in a PDF file shall be transparent.

10) When transparency is used, it must be flattened in the PDF.

## 2. **Images**

- 1) Resolution for color and grey scale images should not be below 300dpi.
- 2) Resolution of 1-bit images (either regular images or image masks) shall not be below 550 dpi.
- 3) Do not use JPEG2000 image compression to reduce file size when exporting PDF files from programs such as InDesign.

## 3. **Colour**

- 1) Color Space must be defined accurately as intended to print (CMYK or Grayscale). When a Pantone/Spot color is required, special arrangement must be made for booking and printing.
- 2) RGB colour must not be used in the PDF.
- 3) Black text shall be in 100% black. To avoid misregistration, rich black (4c black) text is not recommended.
- 4) Fine black text (below 12 point) on 4 colour background must be set to "overprint"
- 5) Coloured text, white text and lines must be set to "knock out".
- 6) Coloured text with a black drop shadow on colour background should be set to "overprint".

## 4. **Fonts Treatment**

- 1) Only PostScript Type 1, TrueType & Open Type are accepted. Avoid using multiple master fonts in one PDF.
- 2) Ensure that all fonts are embedded in the PDF, or convert fonts to outlines to prevent file error.
- 3) All text should be above 8 points for readability. To minimize misregistration, reverse text is recommended to be above 10 points with no more than two colors.

## 5. **File Name**

- 1) Use only alphabet, numbers and underscore "\_".
- 2) For easy identification, file name should contain Advertiser name, Magazine Title, Issue Date.
- 3) In case of revisions, when delivering new files, please name as follows:  
R1\_filename, R2\_filename, and so on.
- 4) PDF should include date and time information.

## 6. **Fogra Standard:**

The SPHMAG Colour Standard has been updated to Fogra Standard (July 2012) as part of our initiative to raise the standard of print reproduction in Singapore. It is aimed at bringing about improvements in print quality of magazines, as well as streamlining the efficiency in advertisements material workflow.

Fogra standard is a pre-requisite for advertisement materials for our titles. To have a better understanding of the standard and procedures, please download the user's kit from <http://www.sphmagazines.com.sg/advertising-specs>

SPHMAG shall not be responsible for any erroneous reproduction of the advertisement copy if the Advertiser of Agency fails to comply with the pre-requisite of file stated in the technical specifications during the production of the advertisement copy or file submission. The technical specifications may be varied and amended by SPHMAG from time to time.

## **Electronic File Transmission (EFT)**

From January 2011 issue, only advertisement materials submitted via two appointed vendors<sup>#</sup>, [Adstream's Quickcut](#) and [Datamation's EADS](#) could be accepted by SPHMAG. They provide a fast and economical solution to validate and transmit files electronically to SPHMAG according to the required technical specifications at a small fee.

As our advertisers, you will enjoy special rates from the appointed vendors. For more information or to set up an account, please contact the following persons:

### 1. **Quickcut**

Lorna Soh at +65 6327 7255 or email at [info@adstream-sg.com](mailto:info@adstream-sg.com)

You can download Quickcut's users guide from <http://www.sphmagazines.com.sg/advertising-specs>

### 2. **EADS**

Cindy Tan at +65 6270 0008 or email at [cindy.tan@datamation.com.sg](mailto:cindy.tan@datamation.com.sg)

Raymond Tang at +65 6270 0008 or email at [raymond@datamation.com.sg](mailto:raymond@datamation.com.sg)

You can download EADS's user's guide from <http://www.sphmagazines.com.sg/advertising-specs>

<sup>#</sup> We welcome other material submission options if the material complies with SPHMAG technical specifications.